


GR-DL-30WB Anti Glare Downlights



Dimension



60°



205

90

Ø 225

Unit:mm

Description&Feature

LED Downlight adopt deep anti-glare desing,delivers a superior LED alternative that'sup to 60% more energy efficient than the conventional downlight retrofits.


It is also ideal for all commercial lighting applications as well as public indoor space where there is limited space in the ceiling.

Its lifetime can be up to 10years.

It is the perfect solution for commercial lighting.

The other extra function such as dimming/ emergency backup / Zigbee also can be available.

Light Distribution Curve



Specification

Model	GR-DL-30WB
Dimension(mm)	Ø225*H90mm
Outcut	Φ195-205mm
Power	30W±5%
LED Chips brand	Epistar/Samsung SMD Led chips
Lumens	2600-3000lm
Color temperature	3000K/4000K-4500K/6000K-6500K
Driver	Included Top quality driver.free flicker
Input voltage	100-240VAC / 220-240VAC 50/60Hz
Power factor	>0.6 or >0.9 if needed
CRI	>80
SDCM	<5
Working life	>50000Hrs
Efficiency	>88%
Materials	Die-cast aluminum+PC,White finished
Beam angle	60°
UGR	<19
IP Grade	IP22 indoor use only
Dimmable	No. but it is ok to do Triac/0-10V/DALI/Zigbee if needed
Working temperature	-30°C~+50°C
Emergency kits	No. but it is ok to do emergency backup for 30% power with 1hrs 2hrs 3hrs duration
Standard	CE LVD EMC RoHs
Warranty	2/3/5Years