


# GR-DL-40WN 9inch COB Downlight



## Dimension



## Description&Feature


LED Downlight adopt top quality aluminum as housing and Osram/CREE/Bridgelux chips, delivers a superior LED alternative that's up to 60% more energy efficient than the conventional downlight retrofits. It is also ideal for all commercial lighting applications as well as public indoor space where there is limited space in the ceiling.

Its lifetime can be up to 10 years.

It is the perfect solution for commercial lighting.

The other extra function such as dimming/emergency backup also can be available.

## Light Distribution Curve



## Specification

Order Model	GR-DL-40WN/9
Dimension(mm)	Ø250*H75mm
Outcut	Φ220-230mm
Power	40W±5%
LED Chips brand	Osram/Bridgelux/CREE COB Led chips
Lumens	3600-4000lm
Color temperature	3000K/4000K-4500K/6000K-6500K
Driver	Philips/Osram/DONE/Eagerise/Boke/LiFud etc Top brand
Input voltage	100-240VAC / 220-240VAC 50/60Hz
Power factor	>0.9
CRI	>92
SDCM	<5 ( <3 available)
Working life	>50000Hrs
Efficiency	>89%
Materials	Die-cast aluminum+Glass cover,White finished
Beam angle	110-120°
IP Grade	IP22 indoor use only
Emergency kits	No. but it is ok to do emergency backup for 30% power with 1hrs 2hrs 3hrs duration
Dimmable	No. but it is ok to do Triac/0-10V/DALI Dimming if needed
Working temperature	-30°C~+55°C
Storage temperature	-35°C~+60°C
Standard	CE LVD EMC RoHs
Warranty	3/5/7Years