# GR-BD-5WF-R Single Head Wall Light

EuroLight™ GRNLED

IP66

## Dimension




Unit:mm

## Description&Feature

This is outdoor wall mounted, made of die-cast aluminum body,toughed glass cover, led chips. Up down lighting. Grey/Black finished options. CRI90 LED Chips and top quality isolated driver, it is very suitable for commercail projects for façade lighting. The standard version is with COB led chips, but also can be GU10 LED bulb optional.

The input voltage 100-240VAC 50/60Hz as standard, but AC/DC12V 24V can be customized as well. What is more, dimmable,motion sensor also can be available if needed.

## Application

## Specification

| | |
|---|---|
| **Order Model** | GR-BD-5WF-R |
| **Diameter(mm)** | L80*W70*H80mm |
| **Outcut** | / |
| **Power** | 5W±5% |
| **LED Chips brand** | Bridgelux Chips |
| **Lumens** | 450-500lm |
| **Color temperature** | 3000K/4000K-4500K/6000K-6500K |
| **Driver** | Isolated driver included |
| **Input voltage** | 100-240VAC / 220-240VAC 50/60Hz |
| **Power factor** | >0.6 |
| **CRI** | >90 |
| **SDCM** | <5 |
| **Working life** | >50000Hrs |
| **Efficiency** | >88% |
| **Materials** | Die-cast aluminum body+Toughed glass cover. Grey /Black finished options |
| **Beam angle** | 30° |
| **IK Rating** | IK07 |
| **IP Grade** | IP66 waterproof |
| **Dimmable** | No.(It is ok to do triac/0-10v/dali if needed) |
| **Working temperature** | -25°C～+60°C |
| **Storage temperature** | -30°C～+65°C |
| **Standard** | CE LVD EMC RoHs |
| **Warranty** | 2/3/5Years options |