
GR-HB-250WM LED High Bay Lights





Dimension



Unit:mm

Description&Feature

LED high bay light with copper heat sink, delivers a superior LED alternative that'sup to 60% more energy efficient than the conventional HPS, Metal halide bay light retrofits.

It is also ideal for all industrial lighting applications as well as public indoor spaces, such as warehouses, bus stations, Mine, Factories., etc.

Its lifetime can be up to 10 years. The other extra function such as dimming/ motion sensor also can be available.

Cover options



| Spacif | ication |
|--------|---------|
| Model | |

 Model
 GR-HB-250WM

 Dimension(mm)
 D350*H424mm

Outcut

Power 250W±5%

LED Chips brand Philips/Osram/Bridgelux SMD3030 252PCS

Lumens 25000-28000lm

Color temperature 3000K/4000K-4500K/6000K-6500K

Driver Isolated driver/Meanwell/Philips/DONE Brand driver

Input voltage 100-240VAC / 220-240VAC 50/60Hz

Power factor >0.95

CRI >80

SDCM <5

Working life >50000Hrs

Efficiency >89%

Materials Die-cast aluminum+Aluminum cover,Black/Silver finished options

Beam angle 25/45/60/90/120° options

THD <15%

IP Grade IP65 waterproof

Dimmable No. but it is ok to do Triac/0-10V/DALI Dimming if needed

Working temperature $-30^{\circ}\text{C} \sim +55^{\circ}\text{C}$

Package 25*25*43CM/PCS/CTNS

Standard CE LVD EMC RoHs

Warranty 2/3/5Years options