

## **GR-SL-400WT LED Street Lights**





## **Dimension**




Unit:mm

## **Description&Feature**

LED Street light, delivers a superior LED alternative that'sup to 60% more energy efficient than the conventional HPS, Metal halide road light retrofits. Top materials such as aluminum housing, isolated driver with 6kv surge protection which will keep its stable quality. The high lumens output will provide the highest brightness.

Its lifetime can be up to 10years. The other extra function such as dimming/ photocell also can be available.

## **Light Distribution Curve**



			_ '		_		4-		
S	-		~	10.0		-		$\sim$	I 'n
L .	•	_						w	

**Standard** 

Warranty

Specification					
Model	GR-SL-400WT				
Dimension(mm)	L953*W300*H78mm				
Installation size	φ60mm				
Power	400W±5%				
LED Chips brand	Philips SMD3030 480pcs				
Lumens	45000-50000lm				
Color temperature	3000K/4000K-4500K/6000K-6500K				
Driver	8pcs*50W Isolated led driver( each driver output is 30V 1.5A)				
Input voltage	85-265VAC 50/60Hz				
Power factor	>0.93				
CRI	>80				
THD	<15%				
Working life	>50000Hrs				
Efficiency	>90%				
Materials	Die-cast aluminum+PC				
Beam angle	70*140°				
Surge protection	4KV				
IP Grade	IP65 waterproof				
Dimmable	No. but it is ok to do Triac/0-10V/DALI Dimming if needed				
Working temperature	-30°C∼+55°C				
Package	430*1000*105mm/pcs/CTN				

CE LVD EMC RoHs

2/3Years options