

- Osram/Bridgelux SMD Chips, 100-130lm/W output, 2700K-6500K
- AC/DC12V/ 24V/36V 48V or 110/220-240VAC,3/5 Years warranty.
- Emergency kits/ Surface/ Suspension installation options.

GR-TP-A Series

PC Bottom+PC Cover
Steel clips



Options



Onekey set the Watt. of the drive



Onekey set the Emergency




Onekey set the Microwave Sensor

Order Model	Power Watt	Dimension mm	CRI	PF	IP Grade
GR-TP-2F1A	10W	600*82*72	>80/90	>0.9	IP65
GR-TP-2F2A	18-20W	600*82*72	>80/90	>0.95	IP65
GR-TP-4F1A	18W	1200*82*72	>80/90	>0.95	IP65
GR-TP-4F2A	36-40W	1200*82*72	>80/90	>0.95	IP65
GR-TP-5F1A	30W	1500*82*72	>80/90	>0.95	IP65
GR-TP-5F2A	50-60W	1500*82*72	>80/90	>0.95	IP65
GR-TP-6F2A	50-60W	1800*82*72	>80/90	>0.95	IP65

GR-TP-B Series


ABS Bottom+PC Cover
Including T8 LED Tube



Order Model	Power Watt	Dimension mm	CRI	Source	IP Grade
GR-TP-2F1B	9W	655*75*86	>80/90	1pcs*2ft T8	IP65
GR-TP-2F2B	2*9W	655*113*86	>80/90	2pcs*2ft T8	IP65
GR-TP-4F1B	18W	1265*75*86	>80/90	1pcs*4ft T8	IP65
GR-TP-4F2B	2*18W	1265*113*86	>80/90	2pcs*4ft T8	IP65
GR-TP-5F1B	22W	1565*75*86	>80/90	1pcs*5ft T8	IP65
GR-TP-5F2B	2*22W	1565*113*86	>80/90	2pcs*5ft T8	IP65

GR-TP-D Series

Whole plastic body+Al heat



Order Model	Power Watt	Dimension mm	CRI	Source	IP Grade
GR-TP-2F2D	20-24W	622*73*51	>80/90	1pcs*2ft T8	IP65
GR-TP-4F2D	40-48W	1223*73*51	>80/90	2pcs*2ft T8	IP65
GR-TP-5F2D	60W	1525*73*52	>80/90	1pcs*4ft T8	IP65

- Osram/Bridgelux SMD Chips, 100-130lm/W output, 2700K-6500K
- AC/DC12V/ 24V/36V 48V or 110/220-240VAC, 2/3 Years warranty.



T5 LED Batten		
Model	Length	Wattage
GR-T5-60	600mm	9W
GR-T5-120	1200mm	18W
GR-T5-150	1500mm	22W



Dust-proof LED Batten IP44		
Model	Length	Wattage
GR-TP-2F2L	600mm	18W
GR-TP-4F2L	1200mm	36W
GR-TP-5F2L	1500mm	45W

GR-TP-G Series

Series connection
Surface mounted



Order Model	Power Watt	Dimension mm	CRI	PF	IP Grade
GR-TP-2F2G	18W	622*50*40	>80/90	>0.9	IP20
GR-TP-4F2G	36W	1223*50*40	>80/90	>0.9	IP20
GR-TP-5F2G	40W	1525*50*40	>80/90	>0.9	IP20



IP65 Waterproof T8 LED Tube		
Model	Length	Wattage
GR-T8-60A	600mm	9W
GR-T8-120A	1200mm	18W
GR-T8-150A	1500mm	22W



T8 LED Tube Light		
Model	Length	Wattage
GR-T860-9W	600mm	9W
GR-T8120-18W	1200mm	18W
GR-T8150-22W	1500mm	22W

GR-TP-N Series

MOQ200PCS/Model
Surfac/pendant



Order Model	Power Watt	Dimension mm	CRI	PF	IP Grade
GR-TP-2F2N	20-30W	622*135*68	>80/90	>0.9	IP20
GR-TP-4F2N	40-60W	1226*135*68	>80/90	>0.9	IP20
GR-TP-5F2N	60-80W	1525*135*68	>80/90	>0.9	IP20