



SURFACE MOUNT DOWNLIGHT

Ref No: GR-FM-30WE



LED Downlight is surface solution, made of metal, aluminum and reflectors. Black/White housing finished available. And it is available to do suspension installation with extra ropes. High CRI, High Lumens output, stable quality, making it to be a perfect choices for commercial lighting.

Complete Product Data

Order Number	GR-FM-30WE
Total Wattage	30W±5%
Mounting Type	Surface mounted as standard; Pendant installation with ropes option
Dimension(mm)	Ø220*120mm
Outcut(mm)	/
IP Grade	IP40
Luminaries Lumens	2800-3200lm
Beam angle	90°
Working temperature	-30°C ~ +55°C
Certificates standard	CE LVD EMC RoHS
Warranty	3/5Years
Package	/

Control Gear Data

LED driver brand	GuanX/LiFud/Eagleries optional
Input voltage	220-240VAC 50/60Hz
Output voltage	30-42Vdc
Output current	700-800mA
Power Factor	>0.5 or 0.9 as standard,
Surge protection	1KV
Efficiency	>86% @230V
IP Grade	IP22
THD	<15% @230V
Dimmable	No, but available to select it as Triac/0-10V/DALI if needed
Free flicker	Yes
Protection	Short circuit, open circuit, overcurrent, overvoltage protection
Certificates	TUV、CCC、RCM、CE、CB
Warranty	3/5Years

Material&Housing Data

Housing Color	Matt white/ black housing color
Housing Material	Aluminum
Cover material	polycarbonate Cover/glass
Reflector	Silver
Lens	/
Surface part	Metal


Photometric Data

LED chip brand	Bridgelux /Osram
Chip type	COB
Color temperature	2700-2800K/3000-3200K/4000-4500K/ 5700-6000K/ 6000-6500K
CRI	>Ra90
Life time	>50000Hrs
Lumens	120-140lm/W
SDCM	<5
Lumens maintenance	99.9%@1000hrs/ 99%@3000hrs /98%@10000hrs. (LM80)

Optional

Dimming Type	Triac dim/ DALI/0-10V dimmable optional
Dimming driver brand	EAGLERISE KOPU
Emergency backup	/
Pendant installation	Suspension ropes is option

Dimension



Unit:mm

Lighting Distribution

