



#### **HIGH LUMEN HIGH BAY LIGHT**

Ref No: GR-HB-400WB-01  $C \in \mathbb{R}^{n}$   $\mathbb{R}^{n}$   $\mathbb{R}^{n}$   $\mathbb{R}^{n}$   $\mathbb{R}^{n}$ 



It is also ideal for all industrial lighting applications as well as public indoor spaces, such as warehouses, bus stations, Mine, Factories., etc..





#### **Complete Product Data**

Order Number	GR-HB-400WB-01
Total Wattage	400W±5%
Install	Suspension as standard; surface mounted available by bracket
Dimension(mm)	Ø490*240mm
IK Rate	IK08
IP Grade	IP54
<b>Luminaries Lumens</b>	56000lm-64000lm
Beam angle	90° as standard; 60°/120° optional
Working temperature	-25°C ~ +60°C
Certificates standard	CE LVD EMC ROHS
Warranty	3/5Years
Package	

#### **Control Gear/Driver Data**

LED driver Type	Moso brand as standard, Philips/Meanwell optional
Input voltage	120-277VAC 50/60Hz
Output voltage	90-250V
Output current	700-2000mA
Power Factor	>0.95
Surge protection	4-6KV
Efficiency	>91% @230V
IP Grade	IP54
THD	<10% @230V
Dimmable	No
Working temperature	-25°C ~ +55°C
Protection	Short circuit, open circuit, overcurrent, overvoltage protection
Certificates	TUV CE ROHS SAA ENEC
Warranty	3/5Years

# Material&Housing Data

Housing Color	Black
Housing Material	Die-cast aluminum
Cover material	PC lens Cover, anti-UV
Reflector	
Bracket	Metal
Cable	High temperature resistant, anti-aging, insulated rubber cable.


# **Photometric Data**

LED chip brand	Philips
Chip type	SMD 2835
Color temperature	3000-3200K/4000-4500K/ 5700-6000K
CRI	>Ra80
Life time	>50000Hrs
Lumens	160-210lm/W
SDCM	<5
Lumens maintenance	99.9%@1000hrs/ 99%@3000hrs /98%@10000hrs. (LM80)

# **Optional**

Dimming Type	PMW/0-10V/DALI dimmable optional
Dimming driver brand	MOSO MAN WELL OSRAM
Emergency kit	9W-18W Battery backup for 1-3hours
Radar sensor	Yes (sensor distance 12-15meter)
Bracket	Yes for surface mounted


### **Dimension**



#### Unit:mm

Bracket

# **Lighting Distribution**



\_\_\_\_\_