

## LOW GLARE DOWNLIGHT

Ref No: GR-DL-7WA-08




LED Downlight adopt deep anti-glare design, it is ok to be different reflector colors option (white/black/silver) and consists of Osram/Bridgelux chips, delivers a superior LED alternative that's up to 60% more energy efficient than the conventional downlight retrofits.

### Complete Product Data

Order Number	GR-DL-7WA-08
Total Wattage	7W±5%
Mounting Type	Recessed
Dimension(mm)	Ø65*H60mm
Outcut(mm)	Ø55mm
IP Grade	IP22
Luminaries Lumens	630-750lm
Beam angle	24° as standard, 15/36° optional
Working temperature	-30°C ~ +60°C
Certificates standard	CE LVD EMC RoHS
Warranty	3/5Years
Package	/

### Control Gear Data

LED driver brand	
Input voltage	220-240VAC 50/60Hz
Output voltage	30-42Vdc
Output current	150-200mA
Power Factor	>0.5 as standard, >0.9 optional
Surge protection	1KV
Efficiency	>87% @230V
IP Grade	IP22
THD	<15% @230V
Dimmable	No, but available to select it as Triac/0-10V/DALI if needed
Free flicker	Yes
Protection	Short circuit, open circuit, overcurrent, overvoltage protection
Certificates	CCC、RCM、CE、CB
Warranty	3/5Years

## Material&Housing Data

Housing Color	Matt white trim+ black heat sink
Housing Material	Aluminum
Cover material	PMMA/Glass
Reflector	polycarbonate, White/black as standard, silver optional
Lens	/
Clips	Metal


## Photometric Data

LED chip brand	Bridgelux as standard, Osram/CREE Optional
Chip type	COB
Color temperature	2700-2800K/3000-3200K/4000-4500K/ 5700-6000K/ 6000-6500K
CRI	>Ra90
Life time	>50000Hrs
Lumens	120-140lm/W
SDCM	<5
Lumens maintenance	99.9%@1000hrs/ 99%@3000hrs /98%@10000hrs. (LM80)

## Optional

Dimming Type	Triac dim/ 0-10V dimmable optional
Dimming driver brand	EAGLERISE <b>KOPU</b> <b>LIFUD</b>
Emergency backup	Battery backup for 1-3W with 1-3hrs duration

## Dimension



Unit:mm

## Lighting Distribution

