


#### **SHAPEABLE TRACK LIGHT**

Ref No: GR-TL-15WT







### **Complete Product Data**

Total Wattage 15W±5%	
Mounting Type Track mounted as standard, surface is optional.	
Dimension(mm) Φ55*190mm	
Outcut(mm) /	
IP Grade IP20	
Luminaries Lumens 1300-1600lm	
Beam angle shapable.	
Working temperature $-25^{\circ}\text{C} \sim +55^{\circ}\text{C}$	
Certificates standard CE LVD EMC RoHS	
Warranty 3/5Years	

#### **Control Gear/Driver Data**

LED driver brand	GuanX/LiFud/Eagleries brand
Input voltage	110/220-240V/277VAC 50/60Hz
Output voltage	30-42Vdc
Output current	350-400mA
Power Factor	>0.5 as standard, >0.88 option
Surge protection	1KV
Efficiency	>87% @230V
IP Grade	IP20
THD	<15% @230V
Dimmable	No, but available to select it as Triac/0-10V/DALI if needed
Free flicker	Yes
Protection	Open Circuit Protection / short Circuit protection/
Certificates	CE CB TUV ENEC
Warranty	3/5Years

## Material&Housing Data

Housing Color	White or black finished
Housing Material	Aluminum
Lens	/
Reflector material	PC reflector
Track heads	Plastic, black/white finished
Connector	/

## **Photometric Data**

LED chip brand	Bridgelux/Osram
Chip type	COB
Color temperature	2700-3000K/3200-3500K/4000-4500K/ 5700-6000K/ 6000-6500K
CRI	>Ra92
Life time	>50000Hrs
Lumens	120-140lm/W
SDCM	<5
Lumens maintenance	99.9%@1000hrs/ 99%@3000hrs /98%@10000hrs. (LM80)

## **Optional**

Dimming Type	Triac dim/ 0-10V dim/ DALI dimmable optic	onal	
Dimming driver brand	Eagleries		
Smart version	Zigbee tuya smart options		
Track Heads	3Wires / 4wires(3 phases) track heads		
		3-wires Track holder	4-wires Track holder

### **Dimension**



#### Unit:mm

# **Lighting Distribution**

