



SURFACE LED PANEL LIGHT

Ref No: GR-PL6060-40WF



This panel light adopts surface mounted design and backlit structure without any LGP, avoiding yellowing change. And it is lens cover for led chips, good lighting performance, all led chips stick on the bottom of fixture, with perfect heat dissipation performance, which will be longer lifetime for luminaires. Widely used for offices, schools, hotels, hospitals etc.

Complete Product Data

| | |
|-----------------------|-----------------|
| Order Number | GR-PL6060-40WF |
| Total Wattage | 40W±5% |
| Mounting Type | Surface mounted |
| Dimension(mm) | 600*600*H40mm |
| Outcut(mm) | / |
| IP Grade | IP44 |
| Luminaries Lumens | 4000-4800lm |
| Beam angle | 120° |
| Working temperature | -30°C ~ +55°C |
| Certificates standard | CE LVD EMC RoHS |
| Warranty | 3/5Years |
| Package | / |

Electrical Data

| | |
|------------------|--|
| LED driver brand | GuanX/LiFud/ Eagleries/Osram brand |
| Input voltage | 110/220-240V/277VAC 50/60Hz |
| Output voltage | 30-42Vdc |
| Output current | 950-1000mA |
| Power Factor | >0.9 |
| Surge protection | 1-2KV |
| Efficiency | >86% @230V |
| IP Grade | IP22 |
| THD | <15% @230V |
| Dimmable | No, but available to select it as Triac/0-10V/DALI if needed |
| Free flicker | Yes |
| Protection | Short circuit, open circuit, overcurrent, overvoltage protection |
| Certificates | CCC、RCM、CE、CB |
| Warranty | 3/5Years |

Material&Housing Data

| | |
|------------------|---------------------|
| Housing Color | White as standard |
| Housing Material | Aluminum trim |
| Cover material | polycarbonate Cover |
| Bottom thickness | >2.5mm |
| Bottom materials | Metal |
| Surface part | Metal |


Photometric Data

| | |
|--------------------|--|
| LED chip brand | Bridgelux / Osram |
| Chip type | SMD 2835 |
| Color temperature | 2700-2800K/3000-3200K/4000-4500K/ 5700-6000K/ 6000-6500K |
| CRI | >Ra80 |
| Life time | >50000Hrs |
| Lumens | 120-150lm/W |
| SDCM | <5 |
| Lumens maintenance | 99.9%@1000hrs/ 99%@3000hrs /98%@10000hrs. (LM80) |

Optional

| | |
|----------------------|--|
| Dimming Type | Triac dim/ 0-10V dim/ DALI dimmable optional |
| Dimming driver brand | EAGLERISE KOPU |
| Emergency backup | Battery backup with 3Hours for 3-5Watt |
| Suspended ropes | / |

Dimension



Unit:mm

Lighting Distribution

