



ALL IN ONE SOLAR STREET LIGHT

Ref No: GR-SSL-80WH

This integrated solar street light is high quality solution, with LifePO4 and Mono solar panel, 3 different installation way. The duration time is 3 raining days. And it is with a adjustable joint, can be installed on top of pole or arm of pole. Available a remote controller. Widely used for governments projects. Working model: Light with sensor, dusk to dawn. During night time, the light will be 100% brightness when there is any movement, but it will be only 30% brightness when there is no any movement.



Complete Product Data

Order Number	GR-SSL-80WH
LED wattage	40W
Install	2 different way options
Dimension(mm)	893*410*35mm
Install pole	60mm
IP Grade	IP65
Beam angle	80*140°
Duration	3-5 raining days
Working temperature	-25°C ~ +55°C
Lumens	8000lm
Warranty	3Years
Install height	6-8meter
Container load qty	380pcs/20ft container; 1030pcs/40ft co
Package Size	923*428*165mm /PCS/CTN

Solar Panel

Solar panel Type	Monocrystalline silicon solar panel
Capacity	18V 60W
Efficiency	>20%
Waterproof	IP65
Lifespan	>25years
Warranty	10years
Dimension(mm)	785*398mm

Sensor & Controller

Type	Microwave radar sensor.
Sensor distance	12-15meter
Photocell sensor	included (dusk to dawn automatically)
Controller	MPPT
Max current	10-20A
Max voltage	12-36V

Battery

Battery type	LifePO4
System voltage	3.2V
Capacity	100Ah
Lifetime	>5 years
Lifespan	>2000 times recycle
Charge time	6 hours by strong sunlight

Photometric Data

LED chip brand	PHILIPS
Chip type	SMD 3030 150PCS *1W
Color temperature	3000-3200K/4000-4500K/ 5700-6000K
CRI	>Ra70
Life time	>50000Hrs
Lumens	180-210lm/W
SDCM	<5
Lumens maintenance	99.9%@1000hrs/ 99%@3000hrs /98%@10000hrs. (LM80)

Lighting Distribution

