


#### **IP65 RECESSED SPOTLIGHT**

Ref No: GR-DL-10WW-02 C €RoHS IP65 △ ※ ▲











#### **Complete Product Data**

Order Number	GR-DL-10WW-02
Total Wattage	10W±5% (7W available)
Mounting Type	Recessed mounted
Dimension(mm)	Ø86*H74mm
Outcut(mm)	Ø75mm
IP Grade	IP65 waterproof
Luminaries Lumens	950-1050lm (650-740lm for 7W)
Beam angle	24°/15/36°
Working temperature	-25℃ ~ +55℃
Certificates standard	CE LVD EMC RoHS
Warranty	3/5Years
Package	

#### **Control Gear/Driver Data**

LED driver brand	LIFU EAGLERISE
Input voltage	220-240VAC 50/60Hz
Output voltage	30-42Vdc
Output current	250-300mA
Power Factor	>0.5 as standard; >0.9 optional
Surge protection	1-2KV
Efficiency	>83% @230V
IP Grade	IP22
THD	<15% @230V
Dimmable	No, but available to select it as Triac/0-10V/DALI if needed
Free flicker	Yes
Protection	Open Circuit Protection / short Circuit protection/
Certificates	ENEC 、CCC、RCM、CE、CB
Warranty	3/5Years

## Material&Housing Data

Outer trim	Aluminum
Housing color	White as standard; black is optional
Heat sink	Die-cast aluminum, black finished
Reflector material	PC reflector, matt white/black/Gun black/silver finish.
Fixation material	Steel
Connector	Ouickly connectors


## **Photometric Data**

LED chip brand	Bridgelux / Osram
Chip type	COB
Color temperature	2700-2800K/3000-3200K/4000-4500K/ 5700-6000K/ 6000-6500K
CRI	>Ra90 (97 Max)
Life time	>50000Hrs
Lumens	120-150lm/W
SDCM	<5
Lumens maintenance	99.9%@1000hrs/99%@3000hrs/98%@10000hrs. (LM80)

## **Optional**

Dimming Type	Triac dim/ 0-10V dim/ DALI dimmable optional
Dimming driver brand	KOPU EAGILERISE OSRAM WEUCHIPS LIFUO
Emergency backup	Battery backup with 1-3Hours for 1-3Watt

#### **Dimension**



Unit:mm

# **Lighting Distribution**

