

#### **TOP RECESSED DOWNLIGHT**

Ref No: GR-DL-25WB-02

CEROHS [ A Z A



This is the top quality recessed fixed led downlight, with a deep & anti-glare design. Its lens is a special structure with up to high lumen output and Bridgelux or OSRAM chips. The trim is white/black optional; and the reflector includes white, black, or matt silver available. Suitable for high-quality commercial projects. The fuction like dimmable, CCT selectable, Zigbee, and emergency can be options.







#### **Complete Product Data**

Order Number	GR-DL-25WB-02
Total Wattage	25W±5% ( 30W Max if needed)
Mounting Type	Recessed mounted
Dimension(mm)	Ø132*75mm
Outcut(mm)	Ø125mm
IP Grade	IP54 waterproof
<b>Luminaries Lumens</b>	2500-3000lm (3000-3500lm for 30W)
Beam angle	50°
Working temperature	-25°C ~ +55°C
Certificates standard	CE LVD EMC RoHS
Warranty	3/5Years
Package	

#### **Control Gear/Driver Data**

LED driver brand	LIFU EAGLERISE
Input voltage	220-240VAC 50/60Hz
Output voltage	30-42Vdc
Output current	600mA; ( 750-800mA for 30W)
Power Factor	>0.5 as standard; >0.9 optional
Surge protection	1KV
Efficiency	>87% @230V
IP Grade	IP20
THD	<15% @230V
Dimmable	No, but available to select it as Triac/0-10V/DALI if needed
Free flicker	Yes
Protection	Open Circuit Protection / short Circuit protection/
Certificates	CCC、RCM、CE、CB
Warranty	3/5Years

## Material&Housing Data

Housing Color	White Trim finished as standard; black trim is optional	
Housing Material	Aluminum	
Heat sink	Die-cast aluminum, black finished	
Reflector material	Aluminum, silver, black and white optional	
Gland	Steel, waterproof	
Connector	Quickly connectors	


### **Photometric Data**

Bridgelux / Osram
SMD/COB
2700-2800K/3000-3200K/4000-4500K/ 5700-6000K/ 6000-6500K
>Ra90
>50000Hrs
140-160lm/W
<5
99.9%@1000hrs/99%@3000hrs/98%@10000hrs. (LM80)


### **Optional**

Dimming Type	Triac dim/ 0-10V dim/ DALI dimmable optional
Dimming driver brand	KOPU EAGILERISE OSRAM WEUCHIPS LIFUO
Emergency backup	Battery backup with 1-3Hours for 2-5Watt

### **Dimension**



# **Lighting Distribution**



\_\_\_\_\_\_