



BROCHURE

Greenriy Technology Co., Limited

info@grnled.com Tel/Whats app:+8613570825764 [Https://grnled.com](https://grnled.com)



Profile

Greenriy Technology Co., Limited/Shenzhen Gelvmei Technology Co., Ltd with brand GRNLED, GOLUMEN, and EuroLight which is especially for Nigeria Market is a professional manufacturer, factory, supplier of Led lights. Established in 2014 at Shenzhen city in China, has grown from its humble origins into an lighting industry leader and the best manufacturer and supplier. By focusing on advanced led technologies and outstanding talent, GRNLED offers professionals and users the solutions and support their need for a wide variety of applications. Our production capacity up to 10000pcs/days for common standard lighting. We pursue the following company culture to create the greatest value for customers.

WHY US

- Certification: ISO9001:2015 listed. And all products are CE Certified, RoHS Compliant.
- One-stop supply: Mostly all types led lights we can produce.
- Better price: Our led lamps are 10%-30% cheaper than other suppliers on the market.
- OEM ODM Service: Accept OEM ODM for different items.
- Faster delivery: Delivery time is fastest, some items is only 1-3days.
- Quality Control: Each lights will be 8-12hours age test before sent out.

WARRANTY

- The basic warranty periods for our led lights is 2-3years, and 5years .
- During guarantee periods, GRNLED provide following supports
- We can send FREELY new products or spares to you if there is any quality issues caused by us within guarantee periods,
- Out of warranty period, It is ok for us to provide extra spares, but all expense for repair and shipping cost should be on customers.

PARTNERS



Factory View



Business License



Export Experience Rights Record



ISO9001:2005



CE



RoHS






Feature

- Philips/LiFud/Eagleries driver brand as standard. 2/3/5Years warranty
- Philips /Bridgelux SMD Chips, CRI>80 or 90, SDCM<3, 100-140LM/W
- Recessed/Suspension/Surface/Clips installation options
- Triac/0-10V/DALI dimmable/Emergency kits/Zigbee smart available.

■ Back-Lit Panel Light

- Stronger Metal bottom , thickness >0.25mm, or 0.3mm. IP44.CCT tunable by dial switch options
- The chassis adopts spray painting technology, which is resistant to high temperature and yellowing



| | | | | | |
|-------------|----------------|----------------|----------------|-----------------|-----------------|
| Order Model | GR-PL3030-18WD | GR-PL6030-20WD | GR-PL6060-40WD | GR-PL12030-40WD | GR-PL12060-80WD |
| Wattage | 18W | 20W | 36/40W/50W | 40W/50W | 50W/60W/72W/80W |
| Size(mm) | 295*295*32 | 595*295*32 | 595*595*32 | 1195*295*32 | 1195*595*32 |

■ Waterproof Backlit LED Panel Light



- Metal bottom thickness: 0.6mm, strongest process by manually.
- Flat Aluminum frame, highest commercial level. IP65 waterproof



| | | | | | |
|-------------|----------------|----------------|----------------|-----------------|-----------------|
| Order Model | GR-PL3030-18WB | GR-PL6030-24WB | GR-PL6060-40WB | GR-PL12030-40WB | GR-PL12060-72WB |
| Wattage | 18W | 20W | 40W | 40W | 72W |
| Size(mm) | 295*295*31 | 595*295*31 | 595*595*31 | 1195*295*31 | 1195*595*31 |

■ Surface LED Panel Light

- IP44 as standard, / IP65 waterproof is options
- Integrated surface frame, brigelux/philips chips, 100lm/w. CRI80/90. 110/220-240VAC.



| | | | | |
|-------------|----------------|----------------|-----------------|-----------------|
| Order Model | GR-PL6030-24WF | GR-PL6060-40WF | GR-PL12030-40WF | GR-PL12060-72WF |
| Wattage | 20W | 40W | 40W | 72W |
| Size(mm) | 600*300*39 | 600*600*39 | 1200*300*39 | 1200*600*39 |

■ Grille LED Panel Light

- White finished as standard; black options
- Recessed type as standard; Surface mounted available




| | | | |
|-------------|------------------|------------------|------------------|
| Order Model | GR-PL6060-40WH-A | GR-PL6060-40WH-B | 3R-PL6060-40WH-C |
| Wattage | 40W | 40W | 40W |
| Size(mm) | 595*595mm | 595*595mm | 595*595mm |


Feature

- LiFud/Eagleries driver brand as standard. 200/240VAC 50/60Hz.
- Philips /Bridgelux SMD Chips, CRI>80 or 90, SDCM<3, 100-140LM/W
- Triac/0-10V/DALI dimmable available.

■ Continuous Pendant Linear Light

- Beam angle: 120°, white/black finished optional.
- Seamlessly connection one by one.



| | | | | |
|-------------|--------------|----------------|---------------|---------------|
| Order Model | GR-L5070-60 | GR-LS-5070-120 | GR-LS5070-150 | GR-LS5070-240 |
| Wattages | 18W | 36W-40W | 44W | 72W-80W |
| Dimension | L585*W50*H70 | L1185*W50*H70 | L1485*W50*H70 | L2390*W50*H70 |


■ Continuous Recessed Linear Light

- Beam angle: 120°, white/black finished optional
- Source: Osram/Bridgelux SMD CRI80 100-129lm/w



| | | | | | |
|-------------|----------------|----------------|----------------|----------------|----------------|
| Order Model | GR-LS-5035-120 | GR-LS-5035-150 | GR-LS-5035-240 | GR-LS-6535-120 | GR-LS-6535-150 |
| Wattages | 36W | 44W | 72W | 36W | 44W |
| Cutout (mm) | L1180*W42 | L1478*W42 | L2378*W42 | L1178*W52 | L1478*W52 |


■ Combination Pendant Linear Light

- Beam angle: 120°+ 24°, white/black finished optional
- Source: Osram/Bridgelux SMD CRI80 100-129lm/w. 110/220-240VAC 50/60Hz.



| | |
|-------------|---------------|
| Order Model | GR-LS6636-36W |
| Wattage | 36W |
| Dimension | L1065*W33*H66 |

■ Round Pendant Linear Light

- Beam angle: 320°, aluminum+PC cover
- Source: Bridgelux SMD CRI80 100-129lm/w. 110/220-240VAC 50/60Hz




| | | |
|-------------|-------------|-------------|
| Order Model | GR-LS60-120 | GR-LS60-150 |
| Wattages | 36W | 45W |
| Dimension | Ø60*L1200 | Ø60*L1500 |



Top Weatherproof led batten

- Beam angle: 120°; PC Bottom+PC Cover. LiFud/Eagleries/Osram driver options, 110/220-240VAC
- Source: Osram/Bridgelux SMD CRI80 100-130lm/w. Radar sensor/Emergency kits options.



| | | | | | | |
|-------------|--------------|--------------|---------------|---------------|---------------|---------------|
| Order Model | GR-TP-2F2A | GR-TP-4F1A | GR-TP-4F2A | GR-TP-5F1A | GR-TP-5F2A | GR-TP-6F2A |
| Wattage | 18W-20W | 20W | 36W-40W | 30W | 50WW | 60W |
| Size(mm) | L600*W82*H72 | L600*W82*H72 | L1200*W82*H72 | L1200*W82*H72 | L1500*W82*H72 | L1500*W82*H72 |



Weatherproof led batten with T8 LED Tube

- Beam angle: 120°; ABS Bottom+PC cover. constant current driver for T8 LED Tube with aluminum body.
- Source: T8 led tube light 100-120lm/w



| | | | | | | |
|-------------|--------------|---------------|---------------|----------------|---------------|----------------|
| Order Model | GR-TP-2F1B | GR-TP-2F2B | GR-TP-4F1B | GR-TP-4F2B | GR-TP-5F1B | GR-TP-5F2B |
| Wattage | 1* 9W led T8 | 2* 9W led T8 | 1* 18W led T8 | 2* 18W led T8 | 1* 22W led T8 | 2* 22W led T8 |
| Size(mm) | L665*W75*H86 | L665*W113*H86 | L1265*W75*H86 | L1265*W113*H86 | L1565*W75*H86 | L1565*W113*H86 |





New Weatherproof led batten

- Beam angle: 120°; IP65; PF>0.9, lumens can be 140lm-160lm/W output.
- Plastic body, available to do linkable series. Constant current driver, stable quality.



| | | | |
|-------------|--------------|--------------|---------------|
| Order Model | GR-TP-2F2S | GR-TP-3F2S | GR-TP-4F2S |
| Wattage | 24W | 30W | 36W |
| Size(mm) | L656*W45*H42 | L956*W45*H42 | L1258*W45*H42 |



IP65 Plastic led batten

| Model | Length | Wattage |
|---------|--------|---------|
| GR-2F2U | 600mm | 18W |
| GR-4F2U | 1200mm | 36W |
| GR-5F2U | 1500mm | 44W |



Aluminum body T8 LED Tube

| Model | Length | Wattage |
|---------------|--------|---------|
| GR-T8600-9W | 600mm | 9W |
| GR-T81200-18W | 1200mm | 18W |
| GR-T81500-22W | 1500mm | 22W |



IP44 dustproof batten

| Model | Length | Wattage |
|------------|--------|---------|
| GR-TP-2F2L | 600mm | 18W |
| GR-TP-4F2L | 1200mm | 36W |
| GR-TP-5F2L | 1500mm | 44W |